


SF6HS

Human dimension of technology



www.newlast.com

SF6HS è la finitrice a tecnologia tradizionale per tre paia di forme.

La macchina SF6 HS consente di eseguire la riproduzione dei file .FRV™ ad elevata velocità, sia nella taglia originale sia nello sviluppo di tutte le altre taglie.

Durante la fase di lavorazione della macchina è inoltre possibile elaborare lo sviluppo della taglia successiva da eseguire o elaborare un modello diverso.





DATI TECNICI/TECHNICAL DATA

N. paia lavorate contemporaneamente/ N. of pairs working at the same time	3 p
Produzione oraria paia/ N. of pairs produced in an hour	60 p/h
Tempo ciclo finitura/ Finishing cycle time	3 min
Ø Max tornibile/ Max turnable Ø	300 mm
Lunghezza massima lavorabile/ Maximum working length	450 mm
Passo di finitura/ Finishing pitch	0.5÷10 mm/rev
Velocità di rotazione/ Rotation speed	10÷120 rev/min÷rev/max
Ø teste di finitura (standard)/ (Standard) finishing-milling heads Ø	90x29 mm
Potenza installata/ installed power	23 Kw
Pressione aria/ Air pressure	6 bar
Peso/ Weight	5000 Kg
Dimensioni/ Dimensions	2850x1900 x2500h mm

SF6 HS is the traditional technology finishing machine for three pairs of lasts.

It allows the fast and accurate execution of .FRV™ in the original and in all the other sizes.

During the working cycle it is also possible to elaborate the next size or a different model.



Newlast Group
Newlast Italia srl · italy@newlast.com
Via G. Pernigotti 31/A · 15057 Tortona (AL)
Tel +39 0131894991 · fax +39 0131814530

